



**NORTH AMERICAN
LUBRICANTS, CO.**

MSDS

Material Safety Data Sheet

Page 1 of 10

Puratech Intake System Cleaner

1. PRODUCT AND COMPANY IDENTIFICATION

Synonyms: None

Product Code: 1101ISC

Generic Name: Intake System Cleaner
Chemical Family: Petroleum Hydrocarbon
Responsible Party: North American Lubricants Company
8502 E. Via De Ventura, Suite 240
Scottsdale, AZ 85258

Help Desk: Mon. – Fri. 7 a.m. – 5 p.m. PST, 1-800-430-6252

EMERGENCY OVERVIEW

24 Hour Emergency Telephone Numbers:

Spill, Leak, Fire or Accident Call CHEMTREC North America: (800) 424-9300 Others: (703) 527-3887 (collect)	California Poison Control System Cont. US: (800) 356-3129 Outside US: (415) 821-5338
---	---

Health Hazards: Harmful: May cause lung damage if swallowed.
Vapors may cause drowsiness and dizziness.

Physical Hazards: Keep away from all sources of ignition.

Environmental Hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Physical Form: Liquid
- Appearance: Clear amber
- Odor: Hydrocarbon odor

<i>Issue Date:</i> 6/22/09	<i>Status: Final New</i>
<i>Revised Sections:</i> New MSDS	

Product Name: Puratech Intake System Cleaner

Page 2 of 10

NFPA HAZARD CLASS: Health: 2 (Hazardous)
Flammability: 2 (Below 200 ° F)
Reactivity: 0 (Stable)
Specific Hazard 0 (None)

2. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENTS

<u>WT%</u>	<u>NAME</u>	<u>SYNONYM</u>	<u>CAS NO.</u>
95.00 – 99.00	Kerosene		8008-20-6
1.00 – 5.00	Methylcyclopentadienyl manganese tricarbonyl		12108-13-3

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

Components not identified are non-hazardous according to 29 CFR 1910.1200

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies for further information.

3. HAZARDS IDENTIFICATION

POTENTIAL HEALTH EFFECTS:

Eye: May cause slight irritation to eyes.

Skin: May cause moderate irritation to skin. Repeated exposure may cause skin dryness or cracking.

Inhalation: Vapors may cause drowsiness and dizziness.

Ingestion: Harmful: may cause lung damage if swallowed.

Signs & Symptoms: If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever. The onset of respiratory symptoms may be delayed for several hours after exposure. Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance. Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Aggravated Medical Condition

:

Pre-Existing Medical Conditions: Pre-existing medical conditions of the following organ(s) or

Issue Date: 6/22/09

Status: Final New

Revised Sections: New MSDS

organ system(s) may be aggravated by exposure to this material: Skin. Respiratory system.

Environmental Hazards : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Additional Information : Under normal conditions of use or in a foreseeable emergency, this product meets the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200 .

4. FIRST AID MEASURES

Eye: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.

Skin: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

Inhalation: Remove to fresh air. If rapid recovery does not occur, transport to nearest medical facility for additional treatment.

Ingestion: If swallowed, do not induce vomiting; transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (37° C), shortness of breath, chest congestion or continued coughing or wheezing.

Note to Physicians: Treat symptomatically. Potential for chemical pneumonitis. Consider: gastric lavage with protected airway, administration of activated charcoal. Call a doctor or poison control center for guidance.

5. FIRE FIGHTING MEASURES

Flammable Properties:

Flash Point:	125 ° F / 52 ° C (CC/ASTM 3278)
OSHA Flammability Class:	Combustible Liquid
LEL/UEL%:	Typical 0.6 / 6 v%
Auto Ignition Temperature:	> 392 °F / 200 °C /

Unusual Fire & Explosion Hazards: Will float and can be reignited on surface water. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds.

Extinguishing Media: Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Do not use water in a jet.

Fire Fighting Instructions: Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space. Isolate immediate hazard area, keep

unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk.

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe all relevant local and international regulations.

Protective Measures : Avoid contact with skin and eyes. Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment (of product and fire fighting water) to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapor or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

Clean Up Methods : Slippery when spilled. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

Additional Advice : Notify fire authorities and appropriate federal, state, and local agencies. Immediate cleanup of any spill is recommended. If spill of any amount is made into or upon navigable waters, the contiguous zone, or adjoining shorelines, notify the National Response Center(phone number 800-424-8802).

7. HANDLING AND STORAGE

General Precautions : Use local exhaust ventilation if there is risk of inhalation of vapors, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material. Keep away from children and animals.

Handling : Extinguish any naked flames. Do not smoke while using this product. Do not wear contaminated clothing or shoes. Wearing contact lenses is inadvisable. Use good personal hygiene practice. Remove ignition sources. Avoid sparks. Avoid prolonged or repeated contact with skin. Avoid inhaling vapor and/or mists. Use only in well ventilated areas. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Storage : Must be stored in a diked, well-ventilated area, away from sunlight, ignition sources

and other sources of heat. Use properly labeled and closeable containers. Keep container tightly closed. Storage Temperature: 32 - 122 °F (0 - 50 °C).

Product Transfer : Electrostatic charges may be generated during handling. Electrostatic discharge may cause fire. Properly ground all equipment.

Recommended Materials : For containers or container linings, use mild steel or high density polyethylene.

Unsuitable Materials : PVC.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Material	Source	Type	ppm	mg/m ³	Notation
Kerosine	ACGIH	TWA(Non-aerosol)		200	As total hydrocarbon vapor
Kerosine	ACGIH	SKIN DES(Non-aerosol)			Can be absorbed through the skin.as total hydrocarbon vapor
Methylcyclopentadienyl manganese tricarbonyl	ACGIH	TWA		0.2	As Mn
Methylcyclopentadienyl manganese tricarbonyl	ACGIH	SKIN DES			Can be absorbed through the skin as Mn.
Methylcyclopentadienyl manganese tricarbonyl	OSHA Z1A	TWA		0.2	As Mn
Methylcyclopentadienyl manganese tricarbonyl	OSHA Z1A	SKIN FINAL			Can be absorbed through the skin as Mn.
Methylcyclopentadienyl manganese tricarbonyl	OSHA Z1	Ceiling		5	As Mn

Exposure Controls : The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances.

Appropriate measures include: Use sealed systems as far as possible. Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Personal Protective Equipment: Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Respiratory Protection : No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.

Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [boiling point >149 °F(65°C)].

Personal Hygiene: Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse. Discard affected clothing, shoes, and/or protective equipment if they cannot be thoroughly cleaned.

Hand Protection : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g., frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

Eye Protection : Wear safety glasses or full face shield if splashes are likely to occur.

Protective Clothing : Skin protection not ordinarily required beyond standard issue work clothes. It is good practice to wear chemical resistant gloves.

Monitoring Methods : Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Environmental Exposure Controls: Minimize release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.

9. PHYSICAL AND CHEMICAL PROPERTIES

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm).

Appearance : Clear amber. Liquid.

Odour : Hydrocarbon.

pH : Not applicable.

Initial Boiling Point and Boiling Range: > 150 °C / 302 °F estimated value(s)

Flash point : 51.7 °C / 125.1 °F (CC / ASTM D3278)

Upper / lower Flammability or Explosion limits: Typical 0.60 - 6 % (V)

Auto-ignition temperature : > 200 °C / 392 °F

Vapor pressure : < 300 Pa at 20 °C / 68 °F (estimated value(s))

Density : 0.84 g/cm³

Water solubility : Negligible.

n-octanol/water partition coefficient (log Pow): > 3

Kinematic viscosity : Data not available

Vapor density (air=1) : > 5 (estimated value(s))

Evaporation rate (nBuAc=1) : Data not available

10. STABILITY AND REACTIVITY

Stability : Stable under normal conditions of storage and handling. .

Conditions to Avoid : Avoid heat, sparks, open flames and other ignition sources.

Materials to Avoid : Strong oxidizing agents.

Hazardous Decomposition Products: Hazardous decomposition products are not expected to form during normal storage.

Hazardous Polymerization : Data not available

Sensitivity to Mechanical Impact: Data not available

11. TOXICOLOGICAL INFORMATION

Basis for Assessment : Information given is based on data on the components and the toxicology of similar products.

Acute Oral Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

Acute Dermal Toxicity : Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit

Acute Inhalation Toxicity : Expected to be of low toxicity: LC50 >20 mg/l / 4 h, Rat. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Skin Irritation : Moderately irritating to skin (but insufficient to classify). Repeated exposure may cause skin dryness or cracking.

Eye Irritation : Expected to be slightly irritating.

Respiratory Irritation : Breathing of high vapor concentrations may cause central nervous system (CNS) depression resulting in dizziness, light-headedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.

Sensitisation : Not expected to be a skin sensitizer.

Repeated Dose Toxicity : Not expected to be a hazard.

Mutagenicity : Not considered a mutagenic hazard.

Carcinogenicity : Not classified as a carcinogen.

Material : Carcinogenicity Classification

Kerosine : ACGIH Group A3: Confirmed animal carcinogen with unknown relevance to humans.

Kerosine : IARC 2A: Probable carcinogen.

Reproductive and Developmental Toxicity: Not expected to be a hazard.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Issue Date: 6/22/09

Status: Final New

Revised Sections: New MSDS

Product Name: Puratech Intake System Cleaner

Page 8 of 10

Acute Toxicity : Poorly soluble mixture. Expected to be toxic: LL/EL/IL50 1-10 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Mobility : Liquid under most environmental conditions. Floats on water. Contains volatile components. Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day. If it enters soil, it will adsorb to soil particles and will not be mobile.

Persistence/degradability : Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product contains components that may persist in the environment. The volatile components oxidize rapidly by photochemical reactions in air.

Bioaccumulation : Contains components with the potential to bioaccumulate.

Other Adverse Effects : Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.

13. DISPOSAL CONSIDERATIONS

Material Disposal : Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.

Container Disposal : Drain container thoroughly. After draining, vent in a safe place away from sparks and fire. Do not, puncture, cut, or weld uncleaned drums. Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

14. TRANSPORT INFORMATION

US Department of Transportation Classification (49CFR)

Identification number UN 1223

Proper shipping name Kerosene

Class / Division 3

Packing group III

Emergency Response Guide No . 128

Additional Information Oil: This product is an oil under 49CFR (DOT) Part 130. If shipped by rail or highway in a tank with a capacity of 3500 gallons or more, it is subject to these requirements. Mixtures or solutions containing 10% or more of this product may also be subject to this rule.

IMDG

Issue Date: 6/22/09

Status: Final New

Revised Sections: New MSDS

Product Name: Puratech Intake System Cleaner

Page 9 of 10

Identification number UN 1223
Proper shipping name KEROSENE
Class / Division 3
Packing group III
Marine pollutant: No
IATA (Country variations may apply)
Identification number UN 1223
Proper shipping name Kerosene
Class / Division 3
Packing group III

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Federal Regulatory Status Notification Status

EINECS	All components listed.
TSCA	All components listed.
DSL	All components listed.

Comprehensive Environmental Release, Compensation & Liability Act (CERCLA)

Methylcyclopentadienyl manganese tricarbonyl (12108-13-3)

SARA Toxic Release Inventory (TRI) (313)

Methylcyclopentadienyl manganese tricarbonyl (12108-13-3) 3.60%

SARA Extremely Hazardous Substances (302/304)

Puratech Intake System Cleaner	Reportable quantity: 2778 lbs
Methylcyclopentadienyl manganese tricarbonyl (12108-13-3)	Reportable quantity: 100 lbs
Methylcyclopentadienyl manganese tricarbonyl (12108-13-3)	Threshold Planning Quantity: 100 lbs

State Regulatory Status

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)

This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

New Jersey Right-To-Know Chemical List

Kerosine (8008-20-6)	Listed.
Methylcyclopentadienyl manganese tricarbonyl (12108-13-3)	Listed.

Pennsylvania Right-To-Know Chemical List

Issue Date:	6/22/09	Status: Final New
Revised Sections:	New MSDS	

Product Name: Puratech Intake System Cleaner

Page 10 of 10

Kerosine (8008-20-6)

Listed.

Methylcyclopentadienyl manganese tricarbonyl (12108-13-3)

Environmental hazard.

Listed.

16. DOCUMENTARY INFORMATION

Issue Date: 6/22/09

17. DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information presented in this Material Safety Data Sheet is based on data believed to be accurate as of the date this Material Safety Data Sheet was prepared. **HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE.** No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

Issue Date: 6/22/09

Status: Final New

Revised Sections: New MSDS