



## **NORTH AMERICAN LUBRICANTS, CO.**

### ***PureSYN DEXRON® VI Transmission Fluid***

PURATECH PureSYN DEXRON® VI ATF is a full-synthetic, premium transmission fluid designed and recommended for use in automatic transmissions that require an approved GM DEXRON® VI fluid (GM license J-60358). It is also backward compatible for use in transmissions previously serviceable by GM DEXRON®-II or DEXRON®-III (H) brands.

PureSYN DEXRON® VI ATF is specially engineered to provide:

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Optimum performance in GM 6-speed transmissions
- Excellent shear stability
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature performance

PureSYN DEXRON® VI ATF's state-of-the-art additive system provides improved shear stability, oxidation resistance and friction durability. This advanced technology delivers ultimate protection and peak performance in passenger cars, SUV's and light trucks.

PureSYN DEXRON® VI ATF also makes an excellent hydraulic fluid in mobile or industrial applications operating in a wide temperature range where low temperature fluidity or leak detection is an important consideration.

#### ***PURATECH PureSYN DEXRON® VI ATF*** **TYPICAL INSPECTION TESTS**

Specific Gravity @ 60° F	0.845
Flash Point, COC C° (F°)	227 (440)
API Gravity	35.6
Viscosity, cP @ -40° C	10,600
Viscosity, cSt @ 40° C	27.3
Viscosity, cSt @ 100° C	6.0
Viscosity Index	175
Pour Point, C° (F°)	-51 (-60)
Color,	Red
Foam Test, ASTM D892	Pass