



## **NORTH AMERICAN LUBRICANTS, CO.**

### ***Puratech Sure-Shift ATF (D-III/M)***

Puratech Sure-Shift ATF is a premium transmission fluid designed and recommended for use in automatic transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands. It may also be used in equipment requiring a “Type A” ATF fluid, Allison C-4, Caterpillar TO-2, and Ford specifications M2C138-CJ and M2C166-H.

Puratech Sure-Shift ATF is formulated to provide:

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Excellent anti-shudder performance
- Good seal compatibility
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature performance

Puratech Sure-Shift ATF’s state-of-the-art additive system provides ultimate protection and peak performance in passenger cars, SUV’s and light trucks. Puratech Sure-Shift ATF is not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V and MERCON® SP fluids.

Puratech Sure-Shift ATF also makes an excellent hydraulic fluid in mobile or industrial applications where low temperature fluidity or leak detection is an important consideration.

#### ***Puratech Sure-Shift (D-III/M)* TYPICAL INSPECTION TESTS**

Density, g/cm <sup>3</sup> @ 15° C	0.860
Flash Point, COC C° (F°)	212 (413)
Viscosity, cP @ -20° C	1300
Viscosity, cP @ -30° C	4200
Viscosity, cP @ -40° C	17000
Viscosity, cSt @ 40° C	35.4
Viscosity, cSt @ 100° C	7.2
Viscosity Index	172
Pour Point, C° (F°)	-52 (-61)
Color,	Red
Foam Test, ASTM D892	Pass